

U.I. Lapp GmbH	PRODUCT INFORMATION	
	Pre-wired front plug for PLC SIMATIC® S7-400	05.11.2015

Single cores used are extra-thin and allow space-saving installation

Info

Crimp, screw and spring model for SIMATIC® S7-400
 We would be glad to help you find solutions for your specific requirements

Product Make-up

The front plugs are in full contact with the single cores of 0.75 mm² or AWG 22 in dark blue (RAL 5010), cores numbered in white according to the allocation in the plug, spacing approx. 20 mm, opposite end cleanly cut
 Conductor end-sleeves or other contacts are available upon request



Norm references / Approvals

For more information on multi-standard single cores, see UL(MTW)-CSA-HAR Style 1015

Product features

Original Siemens-connectors are used exclusively
 The diameter is smaller than that of a H05V-K single core (0.5 mm²)

Remark

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

SIMATIC® is a registered trademark of Siemens AG

Article numbers refer to genuine Lapp products.

Photographs are not to scale and do not represent detailed images of the respective products.

Product Management	Document: LAPP_PRO211EN.pdf	1 / 2
--------------------	-----------------------------	-------



Part number	Colour	mm ²	Length (m)	Copper index kg/1.000 pieces	Weight (kg/1000 pieces)
Pre-wired front plug for PLC SIMATIC® S7-400 (492-1CL00-0AA0) 48-pin, crimp version					
70268421	dark blue (RAL 5010)	0,75	5.0	1695.0	2500
Pre-wired front plug for PLC SIMATIC® S7-400 (492-1AL00-0AA0) 48-pin, screw-on version					
70268423	dark blue (RAL 5010)	0,75	3.0	1017.0	1600
70268424	dark blue (RAL 5010)	0,75	5.0	1695.0	2500
Pre-wired front plug for PLC SIMATIC® S7-400 (492-1BL00-0AA0) 48-pin, spring version					
70260046	dark blue (RAL 5010)	0,75	4.0	1356.0	2000
70268427	dark blue (RAL 5010)	0,75	5.0	1695.0	2500
70260053	dark blue (RAL 5010) - with UL(MTW) single cores	0,5 / AWG22	2.0	442.0	1100